

High Power Contacts (PCB Mount)



DIN 41612, D-Subminiature, Hard Metric

<p>P/N 55-1P-402-1</p>	<p>Max. Current</p>	<p>PCB Layout</p>	
<p>Plug: Right Angle PCB Termination</p>	<p>40 Amp</p>		
<p>P/N 55-1P-412-1</p>	<p>Max. Current</p>	<p>PCB Layout</p>	
<p>Plug: Extended Pin Right Angle PCB Termination</p>	<p>40 Amp</p>		
<p>P/N 55-1S-402-1</p>	<p>Max. Current</p>	<p>PCB Layout</p>	
<p>Socket: Right Angle PCB Termination</p>	<p>40 Amp</p>		
<p>P/N 55-1P-102-1</p>	<p>Max. Current</p>		
<p>Plug: Right Angle PCB Termination</p>	<p>10 Amp</p>		
<p>P/N 55-1P-206-1</p>	<p>Max. Current</p>		
<p>Plug: Extended Pin Right Angle PCB Termination</p>	<p>10 Amp</p>		
<p>P/N 55-1S-102-1</p>	<p>Max. Current</p>		
<p>Socket: Right Angle PCB Termination</p>	<p>10 Amp</p>		

Dimensions are in mm[inch].