

	Recommended Hole Size				Series	A	B
						1500	.100 [2.540]
	Drilled Hole Diameter	Plating Thickness	Hole Diameter	Pad Diameter	1000	.100 [2.540]	.200 [5.08]
	.0453±.001 [1.15]	Copper .001-.003 [.03-.08] Tin .0003 [.008]min.	After Plating .040±.003 [1.02]	.065 [1.65]	1400	.100 [2.540]	.200 [5.08]
					2000	.125 [3.175]	.250 [6.35]
					2400	.125 [3.175]	.125 [3.18]
					2500	.125 [3.175]	.125 [3.18]
					3000	.156 [3.962]	.200 [5.08]
					4000	.150 [3.810]	.200 [5.08]
					4300	.150 [3.810]	.200 [5.08]
					4500	.150 [3.810]	.150 [3.81]
					Series	A	B
					3400	.156 [3.962]	.188 [4.78]
	Drilled Hole Diameter	Plating Thickness	Hole Diameter	Pad Diameter	4600	.150 [3.810]	.188 [4.78]
	.0773±.001 [1.96]	Copper .001-.003 [.03-.08] Tin .0003 [.008]min.	After Plating .072±.003 [1.83]	.097 [2.46]			

Dimensions are in inch [mm]

CARD LAYOUT																	
<table border="1"> <thead> <tr> <th>CONTACT SPACING</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>.100</td> <td>.100 [2.540]</td> <td>.070 [1.78]</td> </tr> <tr> <td>.125</td> <td>.125 [3.175]</td> <td>.080 [2.03]</td> </tr> <tr> <td>.150</td> <td>.150 [3.810]</td> <td>.080 [2.03]</td> </tr> <tr> <td>.156</td> <td>.156 [3.962]</td> <td>.080 [2.03]</td> </tr> </tbody> </table>	CONTACT SPACING	B	C	.100	.100 [2.540]	.070 [1.78]	.125	.125 [3.175]	.080 [2.03]	.150	.150 [3.810]	.080 [2.03]	.156	.156 [3.962]	.080 [2.03]		
CONTACT SPACING	B	C															
.100	.100 [2.540]	.070 [1.78]															
.125	.125 [3.175]	.080 [2.03]															
.150	.150 [3.810]	.080 [2.03]															
.156	.156 [3.962]	.080 [2.03]															
<p>Dim "A" max. = min. Connector Card Slot Length -.001 [.025] Dim "A" min. = min. Connector Card Slot Length -.011 [.28]</p>	<p>1400 Series Only</p>																

Dimensions are in inch [mm]